



SAFETY DATA SHEET

Revision date 27-Jan-2016

Version 1

Supersedes Date: 27-Jan-2016

Section 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Product identifier

Product Code 852SERIES

Product Name 852 Series Mixed Colors

Other means of identification

No information available

Recommended use of the chemical and restrictions on use

Paint, Coatings

Details of the supplier of the safety data sheet

See section 16 for more information

The Valspar Corporation
PO Box 1461
Minneapolis, MN 55440

E-mail address msds@valspar.com

Emergency telephone number

United States of America 1-888-345-5732

American Samoa, Guam, Northern Mariana Islands, Puerto Rico, U.S. Virgin Islands 1-800-255-3924

Section 2: HAZARDS IDENTIFICATION

Classification

Acute toxicity - Inhalation (Dusts/Mists)	Category 4
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2
Skin sensitization	Category 1
Carcinogenicity	Category 1A
Reproductive toxicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 1

Product Code 852SERIES

Page 1 / 14

AGHS - USA OSHA SDS

Aspiration toxicity	Category 1
Flammable liquids	Category 2

Label elements



Signal word

DANGER

HAZARD STATEMENTS

Highly flammable liquid and vapor
 Harmful if inhaled
 Causes skin irritation
 Causes serious eye irritation
 May cause an allergic skin reaction
 May cause cancer
 Suspected of damaging fertility or the unborn child
 Causes damage to organs through prolonged or repeated exposure
 May be fatal if swallowed and enters airways
 May cause respiratory irritation
 May cause drowsiness or dizziness

PREVENTION

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection. Use only outdoors or in a well-ventilated area. Wash face, hands and any exposed skin thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Do not breathe dust/fume/gas/mist/vapors/spray. Do not eat, drink or smoke when using this product. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ ventilating/ lighting/ equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

RESPONSE

IF exposed or concerned: Get medical advice/attention.

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Skin

If skin irritation or rash occurs: Get medical advice/attention. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower. Wash contaminated clothing before reuse.

Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting.

Fire

In case of fire: Use CO₂, dry chemical, or foam for extinction.

STORAGE

Store locked up. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool.

DISPOSAL

Dispose of contents/containers in accordance with local regulations.

HAZARDS NOT OTHERWISE CLASSIFIED (HNOC)

Not applicable.

OTHER HAZARDS

May be harmful if swallowed. May be harmful in contact with skin. Harmful to aquatic life with long lasting effects. Spontaneously combustible material. Risk of self-ignition of used cleaning rags, paper wipes etc. Contaminated materials should be soaked in water and placed in a closed metal container before disposal.

UNKNOWN ACUTE TOXICITY 0% of the mixture consists of ingredient(s) of unknown toxicity.

This document represents the broadest array of ingredient composition, hazard, and precautionary information for coatings produced from specified components of this Valspar product series and mixed according to Valspar instructions. The information presented in this SDS may overstate the actual ingredients contained in and the hazards and precautionary warnings recommended for the particular coating for which it is provided.

Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	weight-%
n-Butyl acetate	123-86-4	10 - 34
Titanium dioxide	13463-67-7	0 - 27
Xylenes	1330-20-7	4 - 16
Methyl acetate	79-20-9	0 - 18
Benzene, 1-chloro-4-(trifluoromethyl)-	98-56-6	0 - 17
Methyl n-amyl ketone	110-43-0	5 - 11
Methyl ethyl ketone	78-93-3	0 - 16
Ethylbenzene	100-41-4	0.9 - 4
Naphtha, petroleum, hydrotreated heavy	64742-48-9	0 - 5
2-Pentanone, 4-methyl-	108-10-1	0 - 5
Solvent naphtha, petroleum, heavy aromatic	64742-94-5	1 - 4
Solvent naphtha, petroleum, light aromatic	64742-95-6	0 - 4
Carbon black	1333-86-4	0 - 3
m-Xylene	108-38-3	0 - 3
Stoddard solvent	8052-41-3	0 - 2
Benzene, 1,2,4-trimethyl-	95-63-6	0 - 2
Toluene	108-88-3	0 - 2
Proprietary additive	Proprietary	0 - 1
Naphthalene	91-20-3	0.1 - 0.4
Proprietary additive	Proprietary	0 - 1
2-Butanone, oxime	96-29-7	0 - 0.3
Proprietary additive	Proprietary	0 - 0.3
Quartz	14808-60-7	0 - 0.2
Proprietary Additive	UNKNOWN	0 - 0.3
Alkanoate ester	Proprietary	0 - 0.3

*The exact percentage (concentration) of composition has been withheld as a trade secret.

Section 4: FIRST AID MEASURES

First Aid Measures

General advice

IF exposed or concerned: Get medical advice/attention.

Eye contact

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Skin Contact

If skin irritation or rash occurs: Get medical advice/attention. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower. Wash contaminated clothing before reuse.

Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Product Code 852SERIES

Page 3 / 14

AGHS - USA OSHA SDS

Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting.

Most important symptoms and effects, both acute and delayed

Symptoms No information available.

Indication of any immediate medical attention and special treatment needed

Note to physicians Treat symptomatically.

Section 5: FIRE FIGHTING MEASURES

Suitable extinguishing media

Dry chemical, CO₂, water spray or alcohol-resistant foam.

Not to be used for safety reasons: Strong water jet

Specific hazards arising from the chemical

Burning produces heavy smoke. Fire may produce irritating and/or toxic gases. In the event of fire and/or explosion do not breathe fumes. May cause sensitization by skin contact. Spontaneously combustible material. Risk of self-ignition of used cleaning rags, paper wipes etc. Contaminated materials should be soaked in water and placed in a closed metal container before disposal. Keep product and empty container away from heat and sources of ignition.

Special protective equipment for fire-fighters

Wear self-contained breathing apparatus and protective suit. Cool containers with flooding quantities of water until well after fire is out. Do not allow run-off from fire-fighting to enter drains or water courses.

Section 6: ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions

Avoid breathing vapors or mists. Remove all sources of ignition. Use personal protective equipment as required. Avoid contact with skin, eyes or clothing. Keep people away from and upwind of spill/leak. Evacuate personnel to safe areas. Take precautionary measures against static discharges.

For emergency responders

Use personal protection recommended in Section 8.

Environmental precautions

Do not allow into any sewer, on the ground or into any body of water. If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations. Prevent further leakage or spillage if safe to do so. Local authorities should be advised if significant spillages cannot be contained.

Methods and material for containment and cleaning up

Methods for containment

Prevent further leakage or spillage if safe to do so.

Methods for cleaning up

Dispose of waste product or used containers according to local regulations. Clean with detergents. Avoid solvent cleaners. Dam up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Pick up and transfer to properly labeled containers. Clean contaminated surface thoroughly. Take up mechanically, placing in appropriate containers for disposal.

Section 7: HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling

Prevent the creation of flammable or explosive concentrations of vapor in air and avoid vapor concentration higher than the occupational exposure limits. Operators should wear anti-static footwear and clothing and floors should be of the conducting type. Use personal protection recommended in Section 8. Never use pressure to empty container. Comply with the health and safety at work laws. Prevent product from entering drains. Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air. Use only with adequate ventilation. Do not breathe dust/fume/gas/mist/vapors/spray. Use only in well-ventilated areas. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Take precautionary measures against static discharges. Use spark-proof tools and explosion-proof equipment. All equipment used when handling the product must be grounded. Risk of self-ignition of used cleaning rags, paper wipes etc. Contaminated materials should be soaked in water and placed in a closed metal container before disposal.

General Hygiene Considerations

When using do not eat, drink or smoke. Wash contaminated clothing before reuse. Avoid contact with skin, eyes or clothing.

Conditions for safe storage, including any incompatibilities

Storage Conditions

Keep/store only in original container. Store in accordance with local regulations. Keep unauthorized personnel away. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Keep container tightly closed in a dry and well-ventilated place. Keep tightly closed in a dry and cool place.

Incompatible materials

Water. Bases. Strong bases. Strong oxidizing agents. Strong acids. Acids. Strong reducing agents. Alkali. Aluminum. Copper. Combustible material. Hydrazine. Amines.

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Limits

If S* appears in the OEL table, it indicates this chemical contains a skin notation.

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
n-Butyl acetate 123-86-4	STEL: 200 ppm TWA: 150 ppm	TWA: 150 ppm TWA: 710 mg/m ³	IDLH: 1700 ppm TWA: 150 ppm TWA: 710 mg/m ³ STEL: 200 ppm STEL: 950 mg/m ³
Titanium dioxide 13463-67-7	TWA: 10 mg/m ³	TWA: 15 mg/m ³ total dust	IDLH: 5000 mg/m ³
Xylenes 1330-20-7	STEL: 150 ppm TWA: 100 ppm	TWA: 100 ppm TWA: 435 mg/m ³	
Methyl acetate 79-20-9	STEL: 250 ppm TWA: 200 ppm	TWA: 200 ppm TWA: 610 mg/m ³	IDLH: 3100 ppm TWA: 200 ppm TWA: 610 mg/m ³ STEL: 250 ppm STEL: 760 mg/m ³
Benzene, 1-chloro-4-(trifluoromethyl)- 98-56-6	TWA: 2.5 mg/m ³ F	TWA: 2.5 mg/m ³ F TWA: 2.5 mg/m ³ dust	
Methyl n-amyl ketone 110-43-0	TWA: 50 ppm	TWA: 100 ppm TWA: 465 mg/m ³	IDLH: 800 ppm TWA: 100 ppm TWA: 465 mg/m ³
Methyl ethyl ketone 78-93-3	STEL: 300 ppm TWA: 200 ppm	TWA: 200 ppm TWA: 590 mg/m ³	IDLH: 3000 ppm TWA: 200 ppm TWA: 590 mg/m ³ STEL: 300 ppm STEL: 885 mg/m ³
Ethylbenzene 100-41-4	TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m ³	IDLH: 800 ppm TWA: 100 ppm TWA: 435 mg/m ³ STEL: 125 ppm STEL: 545 mg/m ³

2-Pentanone, 4-methyl- 108-10-1	STEL: 75 ppm TWA: 20 ppm	TWA: 100 ppm TWA: 410 mg/m ³	IDLH: 500 ppm TWA: 50 ppm TWA: 205 mg/m ³ STEL: 75 ppm STEL: 300 mg/m ³
Carbon black 1333-86-4	TWA: 3 mg/m ³ inhalable fraction	TWA: 3.5 mg/m ³	IDLH: 1750 mg/m ³ TWA: 3.5 mg/m ³ TWA: 0.1 mg/m ³ Carbon black in presence of Polycyclic aromatic hydrocarbons PAH
m-Xylene 108-38-3	STEL: 150 ppm TWA: 100 ppm	TWA: 100 ppm TWA: 435 mg/m ³	IDLH: 900 ppm TWA: 100 ppm TWA: 435 mg/m ³ STEL: 150 ppm STEL: 655 mg/m ³
Stoddard solvent 8052-41-3	TWA: 100 ppm	TWA: 500 ppm TWA: 2900 mg/m ³	IDLH: 20000 mg/m ³ Ceiling: 1800 mg/m ³ 15 min TWA: 350 mg/m ³
Benzene, 1,2,4-trimethyl- 95-63-6	TWA: 25 ppm		TWA: 25 ppm TWA: 125 mg/m ³
Toluene 108-88-3	TWA: 20 ppm	TWA: 200 ppm Ceiling: 300 ppm	IDLH: 500 ppm TWA: 100 ppm TWA: 375 mg/m ³ STEL: 150 ppm STEL: 560 mg/m ³
Naphthalene 91-20-3	TWA: 10 ppm S*	TWA: 10 ppm TWA: 50 mg/m ³	IDLH: 250 ppm TWA: 10 ppm TWA: 50 mg/m ³ STEL: 15 ppm STEL: 75 mg/m ³
Quartz 14808-60-7	TWA: 0.025 mg/m ³ respirable fraction	TWA: (30)/(%SiO ₂ + 2) mg/m ³ TWA total dust TWA: (250)/(%SiO ₂ + 5) mppcf TWA respirable fraction TWA: (10)/(%SiO ₂ + 2) mg/m ³ TWA respirable fraction	IDLH: 50 mg/m ³ respirable dust TWA: 0.05 mg/m ³ respirable dust

Appropriate engineering controls

Engineering Controls

Ensure adequate ventilation, especially in confined areas. Provide local exhaust ventilation. In case of insufficient ventilation, wear suitable respiratory equipment.

Individual protection measures, such as personal protective equipment

Eye/face protection

Tight sealing safety goggles.

Skin and body protection

Wear anti-static clothing made of natural fiber or of high temperature resistant synthetic fiber. Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact. Wear suitable protective clothing.

Hand Protection

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed. Gloves should be replaced regularly and if there is any sign of damage to the glove material. Always ensure that gloves are free from defects and that they are stored and used correctly. The performance or effectiveness of the glove may be reduced by physical / chemical damage and poor maintenance. Wear protective gloves.

Respiratory protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

Thermal Protection

No information available

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state	liquid
Appearance	No information available
Odor	Solvent
Color	No information available
Odor Threshold	No information available
pH value	No information available
Melting point/freezing point	No information available
Boiling point / boiling range	57 °C / 135 °F
flash point	-9 °C / 16 °F
evaporation rate	No information available
Flammability (solid, gas)	No information available
Flammability Limit in Air	
Upper flammability limit:	No information available
Lower flammability limit:	No information available
Vapor Pressure	No information available
vapor density	No information available
Density (lbs per US gallon)	8.5
specific gravity	1.02
Solubility(ies)	No information available
Partition coefficient	No information available
Autoignition temperature	No information available
Decomposition temperature	No information available
Kinematic viscosity	No information available
Dynamic viscosity	No information available

Other information

Section 10: STABILITY AND REACTIVITY

Reactivity	No information available.
Chemical stability	Stable under normal conditions.
Possibility of Hazardous Reactions	None under normal processing.
Hazardous polymerization	None under normal processing.
Conditions to avoid	Heat, flames and sparks.
Incompatible materials	Water. Bases. Strong bases. Strong oxidizing agents. Strong acids. Acids. Strong reducing agents. Alkali. Aluminum. Copper. Combustible material. Hydrazine. Amines.
Hazardous Decomposition Products	Carbon monoxide. Carbon dioxide (CO ₂). Nitrogen oxides (NO _x). Hydrogen chloride. Oxides of sulfur. Chlorine.

Section 11: TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Eye contact

Causes serious eye irritation

Skin Contact

Causes skin irritation

May cause an allergic skin reaction

Ingestion

May be fatal if swallowed and enters airways

Inhalation

May cause respiratory irritation

May cause drowsiness or dizziness

Harmful if inhaled

Numerical measures of toxicity - Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
n-Butyl acetate 123-86-4	= 14.13 mg/kg (Rat)	> 17600 mg/kg (Rabbit)	= 390 ppm (Rat) 4 h
Titanium dioxide 13463-67-7	> 10000 mg/kg (Rat)	-	-
Xylenes 1330-20-7	= 3500 mg/kg (Rat)	> 4350 mg/kg (Rabbit)	= 29.08 mg/L (Rat) 4 h
Methyl acetate 79-20-9	> 5000 mg/kg (Rat)	> 5 g/kg (Rabbit)	= 16000 ppm (Rat) 4 h
Benzene, 1-chloro-4-(trifluoromethyl)- 98-56-6	= 13 g/kg (Rat)	> 2 mL/kg (Rabbit)	= 33 mg/L (Rat) 4 h
Methyl n-amyl ketone 110-43-0	= 1600 mg/kg (Rat)	= 12.6 mL/kg (Rabbit)	> 2000 ppm (Rat) 4 h
Methyl ethyl ketone 78-93-3	= 2483 mg/kg (Rat)	= 5000 mg/kg (Rabbit)	= 11700 ppm (Rat) 4 h
Ethylbenzene 100-41-4	= 3500 mg/kg (Rat)	= 15400 mg/kg (Rabbit)	= 17.2 mg/L (Rat) 4 h
Naphtha, petroleum, hydrotreated heavy 64742-48-9	> 5000 mg/kg (Rat)	> 3160 mg/kg (Rabbit)	-
2-Pentanone, 4-methyl- 108-10-1	= 2080 mg/kg (Rat)	= 3000 mg/kg (Rabbit)	= 8.2 mg/L (Rat) 4 h
Solvent naphtha, petroleum, heavy aromatic 64742-94-5	> 5000 mg/kg (Rat)	> 2 mL/kg (Rabbit)	> 590 mg/m ³ (Rat) 4 h
Solvent naphtha, petroleum, light aromatic 64742-95-6	-	> 2000 mg/kg (Rabbit)	= 3400 ppm (Rat) 4 h
Carbon black 1333-86-4	-	-	-
m-Xylene 108-38-3	= 5000 mg/kg (Rat)	-	-
Stoddard solvent 8052-41-3	-	-	-
Benzene, 1,2,4-trimethyl- 95-63-6	= 3280 mg/kg (Rat)	> 3160 mg/kg (Rabbit)	= 18 g/m ³ (Rat) 4 h
Toluene 108-88-3	= 2600 mg/kg (Rat)	= 12000 mg/kg (Rabbit)	= 12.5 mg/L (Rat) 4 h
Proprietary additive	= 2615 mg/kg (Rat)	-	-
Naphthalene 91-20-3	= 1110 mg/kg (Rat)	= 1120 mg/kg (Rabbit)	> 340 mg/m ³ (Rat) 1 h
Proprietary additive	-	-	-
2-Butanone, oxime 96-29-7	= 930 mg/kg (Rat)	= 0.2 mg/kg (Rabbit)	= 20 mg/L (Rat) 4 h
Proprietary additive	-	-	-
Quartz 14808-60-7	= 500 mg/kg (Rat)	-	-
Proprietary Additive UNKNOWN	-	-	-
Alkanoate ester	-	-	-

Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) 3140 Mg/kg

ATEmix (dermal) 4882 Mg/kg

ATEmix (inhalation-dust/mist) 3.1 mg/l

Product Code 852SERIES

Page 8 / 14

AGHS - USA OSHA SDS

ATEmix (inhalation-vapor) 22 mg/l

UNKNOWN ACUTE TOXICITY 0% of the mixture consists of ingredient(s) of unknown toxicity.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Carcinogenicity

According to IARC, Volume 93, no significant exposure to primary particles of titanium dioxide is thought to occur from use in paints since the pigment is bound to other materials. According to IARC, Volume 93, no significant exposure to primary particles of carbon black is thought to occur from use in paints since the pigment is bound to other materials.

Chemical Name	ACGIH	IARC	NTP	OSHA
Titanium dioxide 13463-67-7		Group 2B		X
Ethylbenzene 100-41-4	A3	Group 2B		X
2-Pentanone, 4-methyl- 108-10-1	A3	Group 2B		X
Carbon black 1333-86-4	A3	Group 2B		X
Naphthalene 91-20-3	A3	Group 2B	Reasonably Anticipated	X
Quartz 14808-60-7	A2	Group 1	Known	X

ACGIH (American Conference of Governmental Industrial Hygienists)

A2 - Suspected Human Carcinogen. A3 - Animal Carcinogen.

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans. Group 2B - Possibly Carcinogenic to Humans.

NTP (National Toxicology Program)

Known - Known Carcinogen. Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen.

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present.

Skin corrosion/irritation	Causes skin irritation
Serious eye damage/eye irritation	Causes serious eye irritation
Skin sensitization	May cause an allergic skin reaction
Respiratory sensitization	Not applicable
Germ cell mutagenicity	Not applicable
Carcinogenicity	May cause cancer
Reproductive Toxicity	Suspected of damaging fertility or the unborn child
Specific target organ toxicity (single exposure)	May cause respiratory irritation May cause drowsiness or dizziness
Specific target organ toxicity (repeated exposure)	Causes damage to organs through prolonged or repeated exposure
Aspiration hazard	Not applicable

Section 12: ECOLOGICAL INFORMATION

Ecotoxicity

Harmful to aquatic life with long lasting effects.

Environmental precautions Prevent product from entering drains.

Persistence and degradability

No information available

Bioaccumulation

No information available

Mobility

No information available

Other adverse effects

No information available

Section 13: DISPOSAL CONSIDERATIONS

Waste treatment methods

- Disposal of wastes** Disposal should be in accordance with applicable regional, national and local laws and regulations.
- Contaminated packaging** Improper disposal or reuse of this container may be dangerous and illegal. Empty containers must be scrapped or reconditioned.

Section 14: TRANSPORT INFORMATION

	<u>DOT</u>	<u>IMDG</u>	<u>IATA</u>
14.1 UN/ID no	UN1263	UN1263	UN1263
14.2 Proper shipping name	Paint	Paint	Paint
14.3 Hazard Class	3	3	3
14.4 Packing Group	II	II	II
14.5 Environmental hazard	Not applicable		
14.6 Special Provisions	149, B52, IB2, T4, TP1, TP8, TP28	163	A3, A72
	Emergency Response Guide Number	EmS-No	
	128	F-E, S-E	
14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	No information available		

The supplier may apply one of the following exceptions: Combustible Liquid (49 CFR 173.150(f)); Consumer Commodity (49 CFR 173.150(c), ICAO/IATA SP A112); Limited Quantity (49 CFR 173.150(b), ICAO Part 3 Chapter 4, IATA 2.7, IMDG Chapter 3.4); Viscous Liquid (49 CFR 173.121(b), IMDG 2.3.2.2, IATA 3.3.3.1.1, ICAO 3.2.2, ADR 2.2.3.1.5); Does Not Sustain Combustion (49 CFR 173.120(a), IATA 3.3.1.3, ICAO 3.1.3, IMDG 2.3.1.3, ADR 2.2.3.1.1 Note 1); or others as allowed under hazardous materials/dangerous goods regulations.

Section 15: REGULATORY INFORMATION

International Inventories

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory All components are listed or exempt from listing.

US Federal Regulations

Chemical Name	TSCA - Toxic Substances Control Act, Section 12(b) Export Notification
Benzene, 1-chloro-4-(trifluoromethyl)- 98-56-6	Section 4

Chemical Name	SARA 313 - Threshold Values %	Hazardous air pollutants (HAPs) content
Xylenes 1330-20-7 4 - 16	1	Present
Aluminum 7429-90-5 0 - 7	1	
Ethylbenzene 100-41-4 0.9 - 4	0.1	Present
2-Pentanone, 4-methyl- 108-10-1 0 - 5	1	Present
m-Xylene 108-38-3 0 - 3	1	Present
C.I. Pigment Yellow 129 15680-42-9 0 - 2	1	

Benzene, 1,2,4-trimethyl- 95-63-6 0 - 2	1	
Toluene 108-88-3 0 - 2	1	Present
PROPRIETARY COPPER COMPOUND UNKNOWN 0 - 2	1.0	
Naphthalene 91-20-3 0.1 - 0.4	0.1	Present

SARA 311/312 Hazard Categories

Acute health hazard	Yes
Chronic Health Hazard	Yes
Fire hazard	Yes
Sudden release of pressure hazard	No
Reactive Hazard	Yes

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
n-Butyl acetate 123-86-4	5000 lb			X
Xylenes 1330-20-7	100 lb			X
Ethylbenzene 100-41-4	1000 lb	X	X	X
m-Xylene 108-38-3	100 lb			X
Toluene 108-88-3	1000 lb	X	X	X
Naphthalene 91-20-3	100 lb	X	X	X

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
n-Butyl acetate 123-86-4	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
Xylenes 1330-20-7	100 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ
Methyl ethyl ketone 78-93-3	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
Ethylbenzene 100-41-4	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ
2-Pentanone, 4-methyl- 108-10-1	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
m-Xylene 108-38-3	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ
Toluene 108-88-3	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ
Naphthalene 91-20-3	100 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ

US State Regulations

Rule 66 status of product

Photochemically reactive.

California Proposition 65

WARNING! This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm.

U.S. EPA Label information

EPA Pesticide registration number Not applicable

Product Code 852SERIES

Page 11 / 14
AGHS - USA OSHA SDS

U.S. State Right-to-Know Regulations

Chemical Name
n-Butyl acetate 123-86-4
Titanium dioxide 13463-67-7
Proprietary Non-Hazardous Ingredient - Proprietary CAS
Proprietary Non-Hazardous Ingredient - Proprietary CAS
Xylenes 1330-20-7
Proprietary Non-Hazardous Ingredient - Proprietary CAS
Proprietary Inert
Methyl acetate 79-20-9
Benzene, 1-chloro-4-(trifluoromethyl)- 98-56-6
Methyl n-amyl ketone 110-43-0
Proprietary Non-Hazardous Ingredient - Proprietary CAS
Proprietary Non-Hazardous Ingredient - Proprietary CAS
Proprietary Non-Hazardous Ingredient - Proprietary CAS
Iron oxide (Fe ₂ O ₃) 1309-37-1
Proprietary Non-Hazardous Ingredient - Proprietary CAS
Proprietary Non-Hazardous Ingredient - Proprietary CAS
Proprietary Non-Hazardous Ingredient - Proprietary CAS
Proprietary Non-Hazardous Ingredient - Proprietary CAS
Aluminum 7429-90-5
Proprietary Non-Hazardous Ingredient - Proprietary CAS
Proprietary Non-Hazardous Ingredient - Proprietary CAS
Methyl ethyl ketone 78-93-3
C.I. Pigment Green 7 1328-53-6
C.I. Pigment Green 36 14302-13-7
Proprietary Non-Hazardous Ingredient - Proprietary CAS
C.I. Pigment Blue 15 147-14-8
Proprietary Non-Hazardous Ingredient - Proprietary CAS
Proprietary Non-Hazardous Ingredient - Proprietary CAS
Ethylbenzene 100-41-4
Naphtha, petroleum, hydrotreated heavy 64742-48-9

2-Pentanone, 4-methyl- 108-10-1
Proprietary Non-Hazardous Ingredient - Proprietary CAS
Proprietary Non-Hazardous Ingredient - Proprietary CAS
Proprietary Non-Hazardous Ingredient - Proprietary CAS
Proprietary Non-Hazardous Ingredient - Proprietary CAS
Proprietary Non-Hazardous Ingredient - Proprietary CAS
Solvent naphtha, petroleum, heavy aromatic 64742-94-5
Solvent naphtha, petroleum, light aromatic 64742-95-6
Carbon black 1333-86-4
m-Xylene 108-38-3
Barium sulfate 7727-43-7
C.I. Pigment Yellow 129 15680-42-9
Stoddard solvent 8052-41-3
Benzene, 1,2,4-trimethyl- 95-63-6
Toluene 108-88-3
Naphthalene 91-20-3
2-Butanone, oxime 96-29-7
Quartz 14808-60-7

Section 16: OTHER INFORMATION

HMIS

Health hazards 3*

* = Chronic Health Hazard

Flammability 3

Physical hazards 1

Personal Protection X

Supplier Address

Valspar Coatings
701 Shiloh Rd.
Garland, TX 75042
972-276-5181

Prepared By Product Stewardship

Revision date 27-Jan-2016

Revision Note No information available

Product Code 852SERIES

Page 13 / 14
AGHS - USA OSHA SDS

Disclaimer

The information on this Safety Data Sheet (SDS) is based on the present state of our knowledge, current national legislation and guidelines. As the specific conditions of use of the product are outside the supplier's knowledge and control the user is responsible for ensuring that the requirements of relevant legislation are complied with. This SDS should not be construed as any guarantee of the technical performance or suitability for particular applications. **UNLESS SUPPLIER AGREES OTHERWISE IN WRITING, SUPPLIER MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. SUPPLIER WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.**

End of Safety Data Sheet