



SAFETY DATA SHEET

Revision date 29-Jan-2016

Version 1

Section 1: PRODUCT AND COMPANY IDENTIFICATION

Product Name LIC40 Series Mixed Colors
Product Code LIC40SERIES
UN/ID no UN1263
Recommended Use Paint, Coatings

Details of the supplier of the safety data sheet

See section 16 for more information

The Valspar Corporation
PO Box 1461
Minneapolis, MN 55440

Valspar Industries, Inc.
1915 Second St. W.
Cornwall, Ontario K6H 5R6

E-mail address msds@valspar.com

Emergency telephone number 1-888-345-5732

Section 2: HAZARDS IDENTIFICATION

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR

HAZARD STATEMENTS

Flammable liquid and vapor.
May cause an allergic skin reaction May cause cancer May cause drowsiness or dizziness Causes skin irritation
Causes serious eye irritation

WHMIS Hazard Class

B2 - Flammable liquid
D2A - Very toxic materials
D2B - Toxic materials



Signal word

DANGER

Product Code LIC40SERIES

Page 1 / 12

WPNA - CANADA WHMIS SDS

PREVENTION

Obtain special instructions before use Use only non-sparking tools Contaminated work clothing should not be allowed out of the workplace Use only outdoors or in a well-ventilated area Do not handle until all safety precautions have been read and understood Wear protective gloves/protective clothing/eye protection/face protection Ground/bond container and receiving equipment Use explosion-proof electrical/ ventilating/ lighting/ equipment Keep container tightly closed Avoid breathing dust/fume/gas/mist/vapors/spray Take precautionary measures against static discharge

RESPONSE

IF exposed or concerned: Get medical advice/attention

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention

Skin

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower If skin irritation or rash occurs: Get medical advice/attention Wash contaminated clothing before reuse

Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing

Ingestion

IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell Do NOT induce vomiting

Fire

In case of fire: Use CO2, dry chemical, or foam for extinction

STORAGE

Store in a well-ventilated place. Keep cool Store in a well-ventilated place Store locked up

DISPOSAL

Dispose of contents/containers in accordance with local regulations

This document represents the broadest array of ingredient composition, hazard, and precautionary information for coatings produced from specified components of this Valspar product series and mixed according to Valspar instructions. The information presented in this SDS may overstate the actual ingredients contained in and the hazards and precautionary warnings recommended for the particular coating for which it is provided.

Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	weight-%
Titanium dioxide	13463-67-7	0 - 35
n-Butyl acetate	123-86-4	8 - 18
Iron oxide (Fe ₂ O ₃)	1309-37-1	0 - 18
Barium sulfate	7727-43-7	0 - 17
Raw umber	12713-03-0	0 - 15
Copper phthalocyanine monochloride	12239-87-1	0 - 11
C.I. Pigment Green 7	1328-53-6	0 - 9
Ethylene glycol monobutyl ether acetate	112-07-2	2 - 6
Carbon black	1333-86-4	0 - 8
Manganese dioxide	1313-13-9	0 - 3
Solvent naphtha, petroleum, light aromatic	64742-95-6	0 - 0.1
Xylenes	1330-20-7	0.2 - 3
Benzene, 1,2,4-trimethyl-	95-63-6	0 - 0.6
Reaction Product Of Methyl Benzotriazol And PEG 300	104810-48-2	0.4 - 0.9
Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	41556-26-7	0.3 - 0.7
Reaction Product Of Benzotriazol Propionate And PEG 300	104810-47-1	0.3 - 0.7
Ethylbenzene	100-41-4	0 - 0.5
Quartz	14808-60-7	0 - 0.4
Methyl Sebacate	82919-37-7	0.1 - 0.3

Section 4: FIRST AID MEASURES

Product Code LIC40SERIES

Page 2 / 12

WPNA - CANADA WHMIS SDS

First Aid Measures

General advice

IF exposed or concerned: Get medical advice/attention

Eye contact

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention

Skin Contact

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower If skin irritation or rash occurs: Get medical advice/attention Wash contaminated clothing before reuse

Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing

Ingestion

IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell Do NOT induce vomiting

Most important symptoms and effects, both acute and delayed

Symptoms No information available.

Indication of any immediate medical attention and special treatment needed

Note to physicians Treat symptomatically.

Section 5: FIRE FIGHTING MEASURES

Flammable properties Flammable liquid.

flash point 81 °F / 27 °C

Upper flammability limit: No information available

Lower flammability limit: No information available

Autoignition temperature No information available

Explosion data

Sensitivity to Mechanical Impact No information available.

Sensitivity to Static Discharge No information available.

Suitable extinguishing media

Dry chemical, CO₂, water spray or alcohol-resistant foam.

Not to be used for safety reasons: Strong water jet

Hazardous combustion products Carbon monoxide. Carbon dioxide (CO₂).

Specific hazards arising from the chemical

Burning produces heavy smoke. Fire may produce irritating and/or toxic gases. In the event of fire and/or explosion do not breathe fumes. May cause sensitization by skin contact.

Special protective equipment for fire-fighters

Wear self-contained breathing apparatus and protective suit. Cool containers with flooding quantities of water until well after fire is out. Do not allow run-off from fire-fighting to enter drains or water courses.

Section 6: ACCIDENTAL RELEASE MEASURES

Personal precautions

Avoid breathing vapors or mists. Remove all sources of ignition. Use personal protective equipment as required. Avoid contact with skin, eyes or clothing. Keep people away from and upwind of spill/leak. Evacuate personnel to safe areas. Take precautionary measures against static discharges.

Environmental precautions

Do not allow into any sewer, on the ground or into any body of water. If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations. Prevent further leakage or spillage if safe to do so. Local authorities should be advised if significant spillages cannot be contained.

Methods for containment

Prevent further leakage or spillage if safe to do so.

Methods for cleaning up

Dispose of waste product or used containers according to local regulations. Clean with detergents. Avoid solvent cleaners. Dam up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Pick up and transfer to properly labeled containers. Clean contaminated surface thoroughly. Take up mechanically, placing in appropriate containers for disposal.

Section 7: HANDLING AND STORAGE

Advice on safe handling

Prevent the creation of flammable or explosive concentrations of vapor in air and avoid vapor concentration higher than the occupational exposure limits. Operators should wear anti-static footwear and clothing and floors should be of the conducting type. Use personal protection recommended in Section 8. Never use pressure to empty container. Comply with the health and safety at work laws. Prevent product from entering drains. Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air. Use only with adequate ventilation. Do not breathe dust/fume/gas/mist/vapors/spray. Use only in well-ventilated areas. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Take precautionary measures against static discharges. Use spark-proof tools and explosion-proof equipment. All equipment used when handling the product must be grounded.

General Hygiene Considerations

When using do not eat, drink or smoke. Wash contaminated clothing before reuse. Avoid contact with skin, eyes or clothing.

Storage Conditions

Keep/store only in original container. Store in accordance with local regulations. Keep unauthorized personnel away. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Keep container tightly closed in a dry and well-ventilated place. Keep tightly closed in a dry and cool place.

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

Exposure Limits

If S* appears in the OEL table, it indicates this chemical contains a skin notation.

Chemical Name	ACGIH TLV	Alberta	British Columbia	Ontario TWA	Quebec	OSHA PEL
Titanium dioxide 13463-67-7	TWA: 10 mg/m ³	TWA: 10 mg/m ³	TWA: 10 mg/m ³ TWA: 3 mg/m ³	TWA: 10 mg/m ³	TWA: 10 mg/m ³	TWA: 15 mg/m ³ total dust
n-Butyl acetate 123-86-4	STEL: 200 ppm TWA: 150 ppm	TWA: 150 ppm TWA: 713 mg/m ³ STEL: 200 ppm STEL: 950 mg/m ³	TWA: 20 ppm	TWA: 150 ppm STEL: 200 ppm	TWA: 150 ppm TWA: 713 mg/m ³ STEL: 200 ppm STEL: 950 mg/m ³	TWA: 150 ppm TWA: 710 mg/m ³
Iron oxide (Fe ₂ O ₃) 1309-37-1	TWA: 5 mg/m ³ respirable fraction	TWA: 5 mg/m ³	TWA: 10 mg/m ³ TWA: 3 mg/m ³ TWA: 5 mg/m ³ STEL: 10 mg/m ³	TWA: 5 mg/m ³	TWA: 5 mg/m ³ TWA: 10 mg/m ³	TWA: 10 mg/m ³ fume TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction
Barium sulfate 7727-43-7	TWA: 5 mg/m ³ inhalable fraction, particulate matter containing no asbestos and <1% crystalline silica	TWA: 10 mg/m ³	TWA: 10 mg/m ³ TWA: 3 mg/m ³	TWA: 10 mg/m ³	TWA: 10 mg/m ³ TWA: 5 mg/m ³	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction

Raw umber 12713-03-0					TWA: 0.2 mg/m ³	Ceiling: 5 mg/m ³ Mn
Copper phthalocyanine monochloride 12239-87-1	TWA: 1 mg/m ³ Cu dust and mist					
C.I. Pigment Green 7 1328-53-6	TWA: 1 mg/m ³ Cu dust and mist					
Ethylene glycol monobutyl ether acetate 112-07-2	TWA: 20 ppm	TWA: 20 ppm TWA: 131 mg/m ³	TWA: 20 ppm	TWA: 20 ppm		
Carbon black 1333-86-4	TWA: 3 mg/m ³ inhalable fraction	TWA: 3.5 mg/m ³	TWA: 3 mg/m ³	TWA: 3 mg/m ³	TWA: 3.5 mg/m ³	TWA: 3.5 mg/m ³
Manganese dioxide 1313-13-9	TWA: 0.02 mg/m ³ Mn TWA: 0.1 mg/m ³ Mn	TWA: 0.2 mg/m ³	TWA: 0.2 mg/m ³ Adverse reproductive effect	TWA: 0.2 mg/m ³	TWA: 0.2 mg/m ³	Ceiling: 5 mg/m ³ Mn
Xylenes 1330-20-7	STEL: 150 ppm TWA: 100 ppm	TWA: 100 ppm TWA: 434 mg/m ³ STEL: 150 ppm STEL: 651 mg/m ³	TWA: 100 ppm STEL: 150 ppm	TWA: 100 ppm STEL: 150 ppm	TWA: 100 ppm TWA: 434 mg/m ³ STEL: 150 ppm STEL: 651 mg/m ³	TWA: 100 ppm TWA: 435 mg/m ³
Benzene, 1,2,4-trimethyl- 95-63-6	TWA: 25 ppm	TWA: 25 ppm TWA: 123 mg/m ³	TWA: 25 ppm	TWA: 25 ppm	TWA: 25 ppm TWA: 123 mg/m ³	
Ethylbenzene 100-41-4	TWA: 20 ppm	TWA: 100 ppm TWA: 434 mg/m ³ STEL: 125 ppm STEL: 543 mg/m ³	TWA: 20 ppm	TWA: 20 ppm	TWA: 100 ppm TWA: 434 mg/m ³ STEL: 125 ppm STEL: 543 mg/m ³	TWA: 100 ppm TWA: 435 mg/m ³
Quartz 14808-60-7	TWA: 0.025 mg/m ³ respirable fraction	TWA: 0.025 mg/m ³	TWA: 0.025 mg/m ³	TWA: 0.10 mg/m ³	TWA: 0.1 mg/m ³	TWA: (30)/(%SiO ₂ + 2) mg/m ³ TWA total dust TWA: (250)/(%SiO ₂ + 5) mppcf TWA respirable fraction TWA: (10)/(%SiO ₂ + 2) mg/m ³ TWA respirable fraction

Engineering Controls

Ensure adequate ventilation, especially in confined areas. Provide local exhaust ventilation. In case of insufficient ventilation, wear suitable respiratory equipment.

Personal Protective Equipment

Eye/face protection

Tight sealing safety goggles.

Hand Protection

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed. Gloves should be replaced regularly and if there is any sign of damage to the glove material. Always ensure that gloves are free from defects and that they are stored and used correctly. The performance or effectiveness of the glove may be reduced by physical / chemical damage and poor maintenance. Wear protective gloves.

Skin and body protection

Wear anti-static clothing made of natural fiber or of high temperature resistant synthetic fiber. Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact. Wear suitable protective clothing.

Respiratory protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators

Thermal Protection

No information available

Environmental exposure controls

Do not allow into any sewer, on the ground or into any body of water. Local authorities should be advised if significant spillages cannot be contained.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

Product Code LIC40SERIES

Page 5 / 12

WPNA - CANADA WHMIS SDS

Information on basic physical and chemical properties

Physical state	liquid
Appearance	No information available
Odor	Solvent
Color	No information available
Odor Threshold	No information available
pH value	No information available
Melting point/freezing point	No information available
Boiling point / boiling range	56 °C / 133 °F
flash point	27 °C / 81 °F
evaporation rate	No information available
Flammability (solid, gas)	No information available
Flammability Limit in Air	
Upper flammability limit:	No information available
Lower flammability limit:	No information available
Vapor Pressure	No information available
vapor density	No information available
Density (lbs per US gallon)	10.16
specific gravity	1.22
Solubility(ies)	No information available
Partition coefficient	No information available
Autoignition temperature	No information available
Decomposition temperature	No information available
Kinematic viscosity	No information available
Dynamic viscosity	No information available

Other information

Section 10: STABILITY AND REACTIVITY

Stability	Stable under normal conditions.
Incompatible materials	None known.
Conditions to avoid	Heat, flames and sparks.
Hazardous Decomposition Products	Carbon monoxide. Carbon dioxide (CO ₂).
Possibility of Hazardous Reactions	None under normal processing.
Hazardous polymerization	None under normal processing.

Section 11: TOXICOLOGICAL INFORMATION

Information on toxicological effects

Information on likely routes of exposure

Eye contact
Not applicable
Skin Contact
Not applicable
Ingestion
Not applicable
Inhalation
Not applicable

Numerical measures of toxicity - Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Titanium dioxide	> 10000 mg/kg (Rat)	-	-
n-Butyl acetate	= 14.13 mg/kg (Rat)	> 17600 mg/kg (Rabbit)	= 390 ppm (Rat) 4 h
Iron oxide (Fe2O3)	> 10000 mg/kg (Rat)	-	-
Barium sulfate	-	-	-
Raw umber	-	-	-
Copper phthalocyanine monochloride	-	-	-
C.I. Pigment Green 7	> 3000 mg/kg (Rat)	-	-
Ethylene glycol monobutyl ether acetate	= 1600 mg/kg (Rat)	= 1480 mg/kg (Rabbit)	-
Carbon black	-	-	-
Manganese dioxide	= 9000 mg/kg (Rat)	-	-
Solvent naphtha, petroleum, light aromatic	-	> 2000 mg/kg (Rabbit)	= 3400 ppm (Rat) 4 h
Xylenes	= 3500 mg/kg (Rat)	> 4350 mg/kg (Rabbit)	= 29.08 mg/L (Rat) 4 h
Benzene, 1,2,4-trimethyl-	= 3280 mg/kg (Rat)	> 3160 mg/kg (Rabbit)	= 18 g/m ³ (Rat) 4 h
Reaction Product Of Methyl Benzotriazol And PEG 300	-	-	-
Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	= 2615 mg/kg (Rat)	-	-
Reaction Product Of Benzotriazol Propionate And PEG 300	-	-	-
Ethylbenzene	= 3500 mg/kg (Rat)	= 15400 mg/kg (Rabbit)	= 17.2 mg/L (Rat) 4 h
Quartz	= 500 mg/kg (Rat)	-	-
Methyl Sebacate	-	-	-

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation	Not applicable
Serious eye damage/eye irritation	Not applicable
Skin sensitization	Not applicable
Respiratory sensitization	Not applicable
Germ cell mutagenicity	Not applicable
Carcinogenicity	Not applicable
Reproductive Toxicity	Not applicable
Specific target organ toxicity (single exposure)	Not applicable
Specific target organ toxicity (repeated exposure)	Not applicable
Aspiration hazard	Not applicable

Carcinogenicity

According to IARC, Volume 93, no significant exposure to primary particles of titanium dioxide is thought to occur from use in paints since the pigment is bound to other materials. According to IARC, Volume 93, no significant exposure to primary particles of carbon black is thought to occur from use in paints since the pigment is bound to other materials.

Chemical Name	ACGIH	IARC	NTP	OSHA
Titanium dioxide		Group 2B		X
Ethylene glycol monobutyl ether acetate	A3			
Carbon black	A3	Group 2B		X
Ethylbenzene	A3	Group 2B		X
Quartz	A2	Group 1	Known	X

ACGIH (American Conference of Governmental Industrial Hygienists)

A2 - Suspected Human Carcinogen

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

NTP (National Toxicology Program)

Known - Known Carcinogen

Section 12: ECOLOGICAL INFORMATION

Ecotoxicity

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Environmental precautions Prevent product from entering drains.

Chemical Name	Algae/aquatic plants	Fish	Crustacea
Titanium dioxide	-	-	-
n-Butyl acetate	= 674.7 mg/L <i>Desmodesmus subspicatus</i> 72 h EC50	= 100 mg/L <i>Lepomis macrochirus</i> 96h LC50 17 - 19 mg/L <i>Pimephales promelas</i> 96h LC50	-
Iron oxide (Fe2O3)	-	-	-
Barium sulfate	-	-	-
Raw umber	-	-	-
Copper phthalocyanine monochloride C.I. Pigment Green 7	-	= 752.4 mg/L <i>Lepomis macrochirus</i> 96h LC50	-
Ethylene glycol monobutyl ether acetate	> 500 mg/L <i>Desmodesmus subspicatus</i> 72 h EC50	-	= 37 mg/L <i>Daphnia magna</i> 48h EC50
Carbon black	-	-	-
Manganese dioxide	-	-	-
Solvent naphtha, petroleum, light aromatic	-	= 9.22 mg/L <i>Oncorhynchus mykiss</i> 96h LC50	= 6.14 mg/L <i>Daphnia magna</i> 48h EC50
Xylenes	-	7.711 - 9.591 mg/L <i>Lepomis macrochirus</i> 96h LC50 23.53 - 29.97 mg/L <i>Pimephales promelas</i> 96h LC50 = 780 mg/L <i>Cyprinus carpio</i> 96h LC50 > 780 mg/L <i>Cyprinus carpio</i> 96h LC50 30.26 - 40.75 mg/L <i>Poecilia reticulata</i> 96h LC50 = 19 mg/L <i>Lepomis macrochirus</i> 96h LC50 = 13.4 mg/L <i>Pimephales promelas</i> 96h LC50 2.661 - 4.093 mg/L <i>Oncorhynchus mykiss</i> 96h LC50 13.5 - 17.3 mg/L <i>Oncorhynchus mykiss</i> 96h LC50 13.1 - 16.5 mg/L <i>Lepomis macrochirus</i> 96h LC50	= 0.6 mg/L <i>Gammarus lacustris</i> 48h LC50 = 3.82 mg/L water flea 48h EC50
Benzene, 1,2,4-trimethyl-	-	7.19 - 8.28 mg/L <i>Pimephales promelas</i> 96h LC50 = 7.72 mg/L <i>Pimephales promelas</i> 96h LC50	= 6.14 mg/L <i>Daphnia magna</i> 48h EC50
Reaction Product Of Methyl Benzotriazol And PEG 300	-	-	-
Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	-	= 0.97 mg/L <i>Lepomis macrochirus</i> 96h LC50	-
Reaction Product Of Benzotriazol Propionate And PEG 300	-	-	-

Ethylbenzene	1.7 - 7.6 mg/L Pseudokirchneriella subcapitata 96 h EC50 > 438 mg/L Pseudokirchneriella subcapitata 96 h EC50 2.6 - 11.3 mg/L Pseudokirchneriella subcapitata 72 h EC50 = 4.6 mg/L Pseudokirchneriella subcapitata 72 h EC50	9.1 - 15.6 mg/L Pimephales promelas 96h LC50 = 9.6 mg/L Poecilia reticulata 96h LC50 = 32 mg/L Lepomis macrochirus 96h LC50 7.55 - 11 mg/L Pimephales promelas 96h LC50 = 4.2 mg/L Oncorhynchus mykiss 96h LC50 11.0 - 18.0 mg/L Oncorhynchus mykiss 96h LC50	1.8 - 2.4 mg/L Daphnia magna 48h EC50
Quartz	-	-	-
Methyl Sebacate	-	-	-

Persistence and degradability No information available.

Bioaccumulation No information available.

Mobility No information available.

Chemical Name	Partition Coefficient (n-octanol/water)
Titanium dioxide	-
n-Butyl acetate	1.81
Iron oxide (Fe2O3)	-
Barium sulfate	-
Raw umber	-
Copper phthalocyanine monochloride	-
C.I. Pigment Green 7	-
Ethylene glycol monobutyl ether acetate	1.51
Carbon black	-
Manganese dioxide	0
Solvent naphtha, petroleum, light aromatic	-
Xylenes	3.15
Benzene, 1,2,4-trimethyl-	3.63
Reaction Product Of Methyl Benzotriazol And PEG 300	-
Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	0.37
Reaction Product Of Benzotriazol Propionate And PEG 300	-
Ethylbenzene	3.118
Quartz	-
Methyl Sebacate	-

Section 13: DISPOSAL CONSIDERATIONS

Waste from residues/unused products Disposal should be in accordance with applicable regional, national and local laws and regulations

Contaminated packaging Improper disposal or reuse of this container may be dangerous and illegal.

Section 14: TRANSPORT INFORMATION

	<u>TDG</u>	<u>IMDG</u>	<u>IATA</u>
UN/ID no	UN1263	UN1263	UN1263
Proper shipping name	Paint related material	Paint related material	Paint related material
Hazard Class	3	3	3
Packing Group	III	III	III
Environmental hazard	Not applicable		
Special Provisions		163, 223, 955	A3, A72
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code		EmS-No F-E, S-E	No information available

Section 15: REGULATORY INFORMATION

Product Code LIC40SERIES
Page 9 / 12
WPNA - CANADA WHMIS SDS

International Inventories

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

All components are listed or exempt from listing

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR

WHMIS Hazard Class

B2 - Flammable liquid
D2A - Very toxic materials
D2B - Toxic materials



Chemical Name	Canada - 2013 NPRI (National Pollutant Release Inventory)
n-Butyl acetate	Part 5, Individual Substances
Raw umber	Part 1, Group A Substance
Copper phthalocyanine monochloride	Part 1, Group A Substance
C.I. Pigment Green 7	Part 1, Group A Substance
Ethylene glycol monobutyl ether acetate	Part 5, Other Groups and Mixtures
Manganese dioxide	Part 1, Group A Substance
Solvent naphtha, petroleum, light aromatic	Part 5, Other Groups and Mixtures
Xylenes	Part 1, Group A Substance Part 5, Isomer Groups
Benzene, 1,2,4-trimethyl-	Part 1, Group A Substance Part 5, Individual Substances
Ethylbenzene	Part 1, Group A Substance

GHS - Classification

Skin sensitization	Category 1
Carcinogenicity	Category 1A
Specific target organ toxicity (single exposure)	Category 3
Flammable liquids	Category 3

Label elements



Signal word

DANGER

HAZARD STATEMENTS

Flammable liquid and vapor
May cause an allergic skin reaction
May cause cancer
May cause drowsiness or dizziness

PREVENTION

Product Code LIC40SERIES

Page 10 / 12

WPNA - CANADA WHMIS SDS

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection. Avoid breathing dust/fume/gas/mist/vapors/spray. Contaminated work clothing should not be allowed out of the workplace. Use only outdoors or in a well-ventilated area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ ventilating/ lighting/ equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

RESPONSE

IF exposed or concerned: Get medical advice/attention.

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Skin

If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.

Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Ingestion

Do NOT induce vomiting. IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.

Fire

In case of fire: Use CO2, dry chemical, or foam for extinction.

STORAGE

Store locked up. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool.

DISPOSAL

Dispose of contents/containers in accordance with local regulations.

HAZARDS NOT OTHERWISE CLASSIFIED (HNOC)

Not applicable.

OTHER HAZARDS

Causes mild skin irritation. Harmful to aquatic life with long lasting effects.

UNKNOWN ACUTE TOXICITY 0% of the mixture consists of ingredient(s) of unknown toxicity.

Section 16: OTHER INFORMATION

HMIS

Health hazards	2*
* = Chronic Health Hazard	
Flammability	3
Physical hazards	0
Personal Protection	X

Supplier Address

Valspar Coatings
701 Shiloh Rd.
Garland, TX 75042
972-276-5181

Prepared By Product Stewardship

Revision date 29-Jan-2016

Revision Note No information available

Disclaimer

The information on this Safety Data Sheet (SDS) is based on the present state of our knowledge, current national legislation and guidelines. As the specific conditions of use of the product are outside the supplier's knowledge and control the user is responsible for ensuring that the requirements of relevant legislation are complied with. This SDS should not be construed as any guarantee of the technical performance or suitability for particular applications. UNLESS SUPPLIER AGREES OTHERWISE IN WRITING, SUPPLIER MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. SUPPLIER WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.

Product Code LIC40SERIES

Page 11 / 12

WPNA - CANADA WHMIS SDS

End of Safety Data Sheet